

Diversey

Complete[®] Floor Finish

A durable finish that reduces the need to strip and refinish – responds beautifully when spray buffed.

Lasts Longer In Tough Traffic Situations

- Low maintenance, high durability and great finish value

Easy-to-Use

- Easy application and recoat
- Great leveling

Simple System Requires Minimal Training

- Easy to clean, maintain and strip with matched Diversey products

Protects and Enhances

- Excellent traffic and mark resistance even on older floors
-



Use Directions

- Strip floor using recommended Diversey brand stripper according to label directions.
- Apply 2–3 uniform coats using a clean mop. If higher gloss is desired, apply additional coats.
- Allow 40–50 minutes drying time between coats.
- Contaminants on floors can cause floors to become slippery.
- Avoid contact with eyes and skin.
- If contact occurs, flush immediately with water.
- If irritation develops, seek medical attention.

Product Specifications

Description	
Color/Form	Opaque tan liquid
Flash Point	>200° F (> 93.3° C)
pH	9.0–9.4
Scent	Ammonia
Shelf Life	2 years
Slip Resistance	0.5 minimum (ASTM D2047-82)
Solids %	17
Solubility	Dispersible
Specific Gravity	1.02

Available Items

Product Code	Description/Package Size	Dilution
04649	4 x 1 gallon / 3.78 L Containers	Ready-to-Use
5104773	1 x 5 gallon / 18.9 L Envirobox™ ^{MC}	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.